

The Quickest Way to Travel



3-wheel

GO GO
ELITE TRAVELLER®



4-wheel

The compact design of the **Go-Go Elite Traveller®** allows you to easily maneuver in tight spaces while providing stable outdoor performance. With a 300 lb. weight capacity, a charger port in the tiller, one-hand feather-touch disassembly and maximum speeds up to 4 mph, it's easy to go where you want to go!



Feather-Touch Disassembly

PRIDE® MOBILITY SCOOTERS
LIVE YOUR BEST®

Mobility Plus of Jacksonville
Call Today! 904 903 7759

Specifications

3W: SC40E 4W: SC44E

Weight Capacity	300 lbs.
Maximum Speed ¹	Up to 4 mph
Ground Clearance ²	1.38" at motor, 0.75" at anti-tip, 2.25" at mid-frame
Turning Radius	3W: 33" 4W: 44"
Overall Length ²	3W: 37" 4W: 39.5"
Overall Width ²	19.5"
Seat-to-Ground Height	18.25" - 20.25"
Seat-to-Deck Height	15.75" - 17.25"
Front Tires	3W: 2" x 8" solid 4W: 2" x 7" solid
Rear Tires	2.5" x 8" solid
Range Per Charge ^{1,4}	3W: Up to 8.5 miles (12 AH) 4W: Up to 8.2 miles (12 AH) 3W: Up to 12.4 miles (18 AH) 4W: Up to 12 miles (18 AH)
Total Weight Without Batteries	3W: 76 lbs. 4W: 80 lbs.
Heaviest Piece When Disassembled	3W: 29 lbs. (front section) 4W: 34 lbs. (front section)
Standard Seating	Type: Foldable, compact, vinyl-covered, molded plastic Weight: 23 lbs. Material: Black Vinyl Dimensions: Width: 17" Depth: 17"
Motor Output	24-volt DC motor, sealed mini-transaxle
Brakes	Regenerative and electromechanical
Battery Requirements ^{3,5}	Size: (2) 12 AH Weight: 9 lbs. each, 20 lbs. per battery pack or Size: (2) 18 AH Weight: 14 lbs. each (optional), 29.5 lbs. per battery pack
Battery Charger	Off-board, 3.5 amp
Colors	2 sets with every scooter!  

Red Blue

Features

- Charger port on tiller
- Convenient dual voltage charger can charge battery pack on-board or off-board
- Feather-touch disassembly permits simple frame separation with only one hand and easily disassembles into five super lightweight pieces for convenient transport and storage
- Front frame-mounted seat post offers maximum stability
- Front tiller-mounted basket
- Includes two sets of easily changeable, red and blue colored panels
- Microprocessor-based controller offers optimal power management and added safety features
- Pride's exclusive black, non-scuffing tires
- Removable footboard basket for additional storage (4-wheel version only)

Accessories

- Cane clip attachment
- Cane/crutch holder (single, double)
- Cup holder
- Forearm crutch holder
- 50" Lap belt
- Oxygen tank holder
- Quad cane holder
- Rear basket
- Rearview mirror
- Saddlebag
- Safety flag
- Under seat storage (assembly required)
- Walker holder
- Weather cover
- Wishbone crutch holder
- XLR USB charger

Accessories

- Additional 12AH battery box
- Additional 18AH battery box

Military Patches



¹ Varies with user weight, terrain type, battery amp-hour (AH), battery charge, battery condition and tire condition. These specifications can be subject to a variance of (+/- 10%).

² Due to manufacturing tolerances and continual product improvement, this specification can be subject to a variance of (+ or - 3%).

³ AGM or gel cell type required.

⁴ Tested in accordance with ANSI/RESNA, WC Vol2, section 4 & ISO 7176-4 standards. Results derived from theoretical calculations based on battery specifications and drive system performance. Test conducted at maximum weight capacity.

⁵ Battery weight may vary based on manufacturer.

NOTE: All specifications subject to change without notice. The information contained herein is correct at the time of publication; we reserve the right to alter specifications without prior notice. Speed and range vary with user weight, terrain type, battery charge, battery condition and tire pressure. Due to manufacturing tolerances and continual product improvement, length, width, turning radius and ground clearance can be subject to variance of + or - 3%. Dimensions listed are for scooter only. Overall measurements will vary based on seating and accessory selections.

Mobility Plus of Jacksonville

Call Today! 904 903 7759



Pride
Mobility Products Corp.